



类型 Type		BM2 100	BM2 125	BM2 160	BM2 200	BM2 250	BM2 315	BM2 400	BM3 500	BM3 630
实际排量 Geometric Displacement (cm ³ /rev.)		100	124.1	164.7	200	248.3	319.2	400	518	666
转速 Max.speed (rpm)	额定 rated	400	400	310	250	200	150	125	160	125
	断续 int.	500	500	400	310	250	200	150	200	160
扭矩 Max. torque (N · m)	额定 rated	198	215	285	347	385	495	477	772	993
	断续 int.	241	268	355	459	470	568	620	1054	1355
输出功率 Max. output (kW)	额定 rated	8.1	8.8	9	9	8	8	6	13	13
	断续 int.	9.6	11	11	11	10	9	9	17	17
工作压差 Max. pressure drop (MPa)	额定 rated	16	14	14	14	12.5	12.5	10	12.5	12.5
	断续 int.	19	17	17	17	14	14	12.5	16	16
进油压力 Max. inlet pressure (MPa)	额定 rated	20	20	20	20	20	20	20	20	20
	断续 int.	25	25	25	25	25	25	25	25	25
重量 weight (kg)		6.7	7.2	7.8	8.1	8.4	9.0	9.5	17.5	18.5



类型 Type	BMP BMPH BMP1 BMPG 50	BMP BMPH BMP1 BMPG 80	BMP BMPH BMP1 BMPG 100	BMP BMPH BMP1 BMPG 125	BMP BMPH BMP1 BMPG 160	BMP BMPH BMP1 BMPG 200	BMP BMPH BMP1 BMPG 250	BMP BMPH BMP1 BMPG 315	BMP BMPH BMP1 BMPG 400
实际排量 Geometric displacement(cm ³ /rev.)	51.7	77.7	96.2	117.9	155.5	189.9	231	311.7	386.2
转速 Max. Speed (rpm)	额定 rated	850	650	520	390	310	260	200	130
	连续 cont.	879	740	598	475	370	296	237	149
	断续 int.	975	827	673	594	463	370	297	185
扭矩 Max. torque(N · m)	额定 rated	81	129	161	202	204	259	325	435
	连续 cont.	81	129	161	202	245	286	360	435
	断续 int.	108	171	213	268	342	390	456	533
输出功率 Max.output (kW)	额定 rated	7	8.6	8.6	8	6.5	6.9	6.6	5.8
	连续 cont.	7	9.1	9	9.1	8.7	8.1	8.2	7.2
	断续 int.	8.9	11.8	11.9	11.8	11.9	10.9	10.1	8.6
工作压力 Max. pressure drop (MPa)	额定 rated	12.5	12.5	12.5	12.5	10	10	10	8.5
	连续 cont.	12.5	12.5	12.5	12.5	12.5	11	11	11
	断续 int.	16.5	16.5	16.5	16.5	16.5	16.5	14	12.5
	峰值 peak	16.5	16.5	16.5	16.5	16.5	16.5	14	12.5
流量 Max. flow(L/min)	额定 rated	45	55	55	55	55	55	55	55
	连续 cont.	45	60	60	60	60	60	60	60
	断续 int.	50	75	75	75	75	75	75	75
重量 weight (kg)	5.6	5.7	5.9	6	6.2	6.4	6.6	6.9	7.4



类型 Type		BMR BMSR BMRL 50	BMR BMSR BMRL 80	BMR BMSR BMRL 100	BMR BMSR BMRL 125	BMR BMSR BMRL 160	BMR BMSR BMRL 200	BMR BMSR BMRL 250	BMR BMSR BMRL 315	BMR BMSR BMRL 375
排量 Geometric displacement (cm ³ /rev.)		51.3	80	100.8	124.9	157.2	199.2	252	314.5	370
转速 Max. speed (rpm)	额定 rated	755	750	600	475	375	300	240	190	160
	连续 cont	970	940	750	600	470	375	300	240	200
扭矩 Max. torque (N m)	额定 rated	100	160	200	250	320	330	352	360	420
	连续 cont	100	190	240	292	363	358	352	360	420
	断续 int	126	220	280	340	430	448	470	470	548
输出功率 Max. output (kW)	额定 rated	7.7	12.3	12.3	12.0	12.3	10	9	7	6.5
	连续 cont	7.7	15	15	14	14	11	9	7	8.6
	断续 int	9.7	17	17	16	16	14	12	9	12
工作压力差 Max. pressure Drop (MPa)	额定 rated	14	14	14	14	14	12	11	8.5	8.5
	连续 cont	14	17.5	17.5	17.5	16.5	13	11	8.5	8.5
	断续 int	17.5	20	20	20	20	17.5	14	11.5	11.5
流量 Max. flow (L/min)	连续 cont	40	60	60	60	60	60	60	60	60
	断续 int	50	75	75	75	75	75	75	75	75
重量 weight (kg)		6.7	6.9	6.9	7.2	7.5	8.0	8.5	9	9.3